



Vancouver
ARCHITECTURAL DOORS

90 Minute Fire Rated Flush Door Mineral Core - 790M (1-1/2 Hour)



Top/Bottom Rail and Stiles: 1.5" thick minimum
LEX REM HD Composite Material

Vertical Stiles: 1/2" thick matching wood stile before trim; 1/4" Max wood stile after trim.

Core: LEX Mineral Core

Core/Edge Interface: Stiles and Rails are bonded to core and core assembly is sanded prior to application of crossband and veneer.

Crossband backer for wood veneered doors

Faces: Options include Standard or Custom Wood Veneer minimum 1/50"; Medium Density Overlay or Hardboard; High Pressure Laminate;

Maximum door size: 4'0" x 9'0" (Singles) 7'0 x 9'0" (Pairs)

Thickness options: 1-3/4" Standard (2-1/4" Optional)

Fire Ratings: 90 Minutes – Meets UL 10B/ 10C & NFPA 252 standards (some restrictions apply)

STC Sound Rating: Up to STC 37

Warranty: Limited Lifetime (see warranty sheet for details)

LEED Options: Recycled Content | No Added Formaldehyde | CARB Phase II

Manufacturing Location: San Antonio, TX USA

Veneer Options: Wood veneers (standard & custom) | MDO or Hardboard | High Pressure Decorative Laminate (HPDL)

Finishing Options: Unfinished | Primed | Clear Coat | Custom Color Finish (Conversion Varnish)

Specialty Options: Raised Moldings | Matching Fire Rated Wood Frames